



Material: A6063-T5 / Clear Anodize  
Mass: 0.80 kg./m.

4-6 M. MAX. LENGTH




Material: A6063-T5 / Clear Anodize  
Mass: 0.93 kg./m.

4-6 M. MAX. LENGTH




Material: A6063-T5 / Clear Anodize  
Mass: 0.82 kg./m.

4-6 MAX. LENGTH




Material: A6063-T5 / Clear Anodize  
Mass: 1.50 kg./m.

4-6 M. MAX. LENGTH




Material: A6063-T5 / Clear Anodize  
Mass: 1.63 kg./m

6 M. MAX. LENGTH




Material: A6063-T5 / Clear Anodize  
Mass: 2.44 kg./m.

4 M. MAX. LENGTH




Material: A6063-T5 / Clear Anodize  
Mass: 3.21 kg./m.

4 M. MAX. LENGTH




Material: A6063-T5 / Clear Anodize  
Mass: 0.85 kg./m.

4 M. MAX. LENGTH




Material: A6063-T5 / Clear Anodize  
Mass: 0.86 kg./m.

4 M. MAX. LENGTH



Material: A6063-T5 / Clear Anodize  
Mass: 0.89 kg./m.


4 M. MAX. LENGTH



Material: A6063-T5 / Clear Anodize  
Mass: 0.90 kg./m.


4 M. MAX. LENGTH

**DCM-30**




Mat'l: ADC12 Aluminum Die Cast  
Allowable Load: 117 kgf.  
Applicable Parts:

M6 x 12 2 PCS.




**DC-30**




Mat'l: ADC12 Aluminum Die Cast  
Allowable Load: 125 kgf.  
Applicable Parts:

M6 x 12 2 PCS.




**HB-30**




Mat'l: A6063-T5 / Clear Anodize  
Allowable Load: 117 kgf.  
Applicable Parts:

M6 x 16 2 PCS.




**LB-30**




Mat'l: A6063-T5 / Clear Anodize  
Allowable Load: 98 kgf.  
Applicable Parts:

M6 x 12 2 PCS.




**DCS-30**




Mat'l: ADC12 Aluminum Die Cast  
Allowable Load: 117 kgf.  
Applicable Parts:

M6 x 12 2 PCS.




**HB-4H-30**




Mat'l: A6063-T5 / Clear Anodize  
Allowable Load: 303 kgf.  
Applicable Parts:

M6 x 16 4 PCS.




DCM-4H-30




Mat'l: A6063-T5 / Clear Anodize  
Allowable Load: 303 kgf.  
Applicable Parts:

M6 x 12 4 PCS.




LB-3060




Mat'l: A6063-T5 / Clear Anodize  
Allowable Load: 156 kgf.  
Applicable Parts:

M6 x 12 4 PCS.




HB-3060




Mat'l: A6063-T5 / Clear Anodize  
Allowable Load: 196 kgf.  
Applicable Parts:

M6 x 16 4 PCS.




DCM-3060




Mat'l: ADC12 Aluminum Die Cast  
Allowable Load: 294 kgf.  
Applicable Parts:

M6 x 12 8 PCS.




DC-3060




Mat'l: ADC12 Aluminum Die Cast  
Allowable Load: 282 kgf.  
Applicable Parts:

M6 x 16 4 PCS.




HB-8H-3060




Mat'l: A6063-T5 / Clear Anodize  
Allowable Load: 294 kgf.  
Applicable Parts:

M6 x 16 8 PCS.



HB-3090



Mat'l: A6063-T5 / Clear Anodize  
Allowable Load: 274 kgf.  
Applicable Parts:

M6 x 16 6 PCS.

